

Serial to Ethernet Converter


■ ■ ■ USR-TCP232-T2

Serial Ethernet data transmission

USR-TCP232-T2 is a tiny size serial TTL UART to Ethernet module which can realize data bidirectional transparent transmission between TTL and RJ45 port. It can also be applied in rs232/ rs485 by level shift circuit. USR-TCP232-T2 is based on Cortex-M0 core. It has characters of low power, fast speed and high efficiency.

■ ■ ■ TTL to Ethernet

- Support DNS function
- Support DHCP, automatically obtain an IP address and query IP address through serial setting protocol
- Set parameter through webpage and serial AT command
- Serial port baud rate from 600 bps to 460.8 Kbps, Check bit of None, Odd, Even, Mark and Space
- Upgrade firmware via network
- Work mode: TCP Server, TCP Client, UDP Client, UDP Server, HTTPD Client
- Auto-MDI/MDIX, RJ45 port with 10/100Mbps
- Restore factory default
- Heartbeat package mechanism to ensure connection is reliable, put an end to dead link
- User-defined registration package mechanism, check connection status and use as custom packet header
- The global unique MAC address bought from IEEE, user can define MAC address
- Across the gateway, switches, routers
- Support virtual serial port and provide corresponding software USR-VCOM
- Under TCP Server mode, Client number ranges from 1 to 16; default number is 4
- Can work in LAN, also can work in the Internet
- Provide PC TCP/IP socket programming example such as VB, C++, Delphi, Android and IOS
- Support customization



Specifications	
System Information	
Processor	ARM
Flash	32K byte
Serial	
Port Number	1
Interface Standard	TTL
Data Bit	5, 6, 7, 8
Stop Bit	1, 2
Check Bit	None, Even, Odd, Space, Mark
Baud Rate	600 bps ~ 460.8 Kbps
Buffer	Receive: 800 bytes
RS485 Pull-up and Pull-Down Resistor	Null, reserved 485 send-receive control pin
Ethernet	
Rate	10/100 Mbps, MDI/MDIX, auto switch between cross and direct connection
Interface Standard	RJ45
Port Number	1
Network Protocol	IP, TCP, UDP, DHCP, DNS, HTTP, ARP, ICMP
Protection	2KV electromagnetism isolation
Buffer	Send: 6K bytes Receive: 4K bytes
Basic Parameter	
Size	55 x 22.6 x 23.1 mm
Operating Temp.	-25 ~ 75°C
Storage Temp.	-40 ~ 105°C, 5 ~ 95% RH
Input Voltage	DC 3.3V/5V
Working Current	150mA
Software	
Virtual Serial	Windows 2000 or higher (32 bit/64 bit)
Configuration	Computer set-up software Serial command Built-in webpage AT command

Jinan USR IOT Technology Limited

Tel: 86-531-88826739

Email: sales@usriot.com

Web: www.usriot.com

Support: h.usriot.com

