MEC-LAN-M001

Mini PCI-e 1-port 10/100/1000 Ethernet board



- PCI Express x 1 compliant
- Integrated 10/100/1000Mbps transceiver
- IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, and IEEE 802.3z compliant
- IEEE 802.3x Full-Duplex flow control











Overview

MEC-LAN-M001 is an Ethernet card for embedded PC. The card follows the Mini PCI-e standard which is compliant with PCI Express x 1 classification and small form factor (30×50.95 mm). This board fits in any host computer that has Mini PCI-e card slots. MEC-LAN-M001 is a highly cost-effective solution to expand Gigabyte network for your computer.

Top Performance

MEC-LAN-M001 has one Ethernet port that supports auto-negotiation 10/100/1000Mbps Ethernet connection with IEEE 802.3x flow control.

Intel Ethernet Chipset

MEC-LAN-M001 uses high performance, efficiency, and stability Intel 82583V Gigabit Ethernet Controller.



High Usability


MEC-LAN-M001 is designed with flexibilities for many different application and accessories (daughter board, bracket, connection cable) are included in the standard package.



MECFIX - Versatile Mounting

MECFIX is the unique mounting mechanism designed specially for MEC daughterboard. The feature of the mounting unit allows the following mounting options:

- 1. Standard PCI/PCIe Bracket
- 2. Low Profile PCI/PCIe Bracket
- 3. Internal Mounting inside of PC system from any position and angle.
- 4. Customizing Front/Rear Plate of PC system according to dimension of MEC daughterboard.



Specifications

Hardware

Controllers: Intel 82583V Gigabit Ethernet

Bus: PCI Express X1

Interface (Connector)

Ethernet 10/100/1000: 1 (RJ45)

Technology

Standards: • IEEE 802.3 for 10BaseT

IEEE 802.3u for 100BaseT(X)
IEEE 802.3ab for 1000BaseT(X)
IEEE 802.3z for 1000BaseX

Flow Control: IEEE 802.3x flow control

Driver Support


Operating Systems: Win 2003, Win XP,

Win Vista, Win 7, Win 8

Power Requirement

Power Consumption: 250mA@3.3V

Dimensions



Pa Pa

Package Checklist

- Mini PCI-e Card x 1
- Daughter Board x 1
- Bracket x 1
- M2.5 Screw x 2
- 20Pin Internal Cable (30cm) x 1
- Quick Installation Guide (Printed) x 1
- Driver CD x 1

Ordering Information



Available Models

Dimensions

Width x Length (mm): 30.00 x 50.95

Environmental Limits

Operating Temperature: -20°C ~ 70°C **Storage Temperature:** -20°C ~ 85°C

Humidity: 5% ~ 95%

Regulatory Approvals

EMC: CE, FCC

EMI: EN 55022, EN61000-3-2, EN61000-3-3,

FCC Part 15 Subpart B

Class B

EMS: En 55024, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6.

IEC 61000-4-8, IEC 61000-4-11

Reliability

MTBF: 2,872,737 hr Warranty: 3 years

