

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [1200845013](#)
Status: **Active**
Overview: [Brad Ultra-Lock Connection System](#)
Description: Micro-Change (M12) Receptacle, 12 Poles, Female (Straight) to Leads, 0.30m (11.81") Length

Documents:
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

Agency Certification
CSA LR6837

General
Product Family Industrial Receptacles
Series [120084](#)
IP Rating IP69K
NEMA Rating NEMA 6
Overview [Brad Ultra-Lock Connection System](#)
Product Name Ultra-Lock (M12)
Type Single Ended (pigtail)
UPC 883906540807

Physical
Coupling Type Internal Thread
Gender Female
Keyway Single
Length 0.30m
Material - Component Nickel-plated Brass
Mounting Thread Size M16 x 1.5
Net Weight 27.800/g
Orientation Straight
Panel Mount Front
Poles 12
Temperature Range - Operating -25°C to +90°C
Wire Size AWG 26
Wire/Cable Type Leads, UL 1061

Electrical
Current - Maximum per Contact 1.5A
Voltage - Maximum 30V AC/DC

Material Info
Engineering Number WRCU20E01C300

Reference - Drawing Numbers
Sales Drawing 1200845013-000



Series image - Reference only

EU ELV
Not Relevant

EU RoHS **China RoHS**
Compliant with Exemption 6(c),7(c)-I
REACH SVHC
Contained Per - ED/71/2019 (16 July 2019)
Lead
Halogen-Free
Status
Not Low-Halogen
For more information, please visit [Contact US](#)

China ROHS	50 Image
ELV	Not Relevant
RoHS Phthalates	Not Contained

Search Parts in this Series
[120084](#) Series

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION